

## Gina Mary



## 25m Twin Screw Aquaculture Support Vessel - MCA Cat 1 - 150 miles offshore

- capacity for 3 x ISO, twin line hydrolicer, anchor handling & towing
- large clear deck area for de-licing operations
- general heavy site service duties
- bollard pull approx 15 ton
- deck cargo 115 ton; capacity for 5 x 20 ft containers
- fuel and water transfer







## Gina Mary Specifications

| General:                              | Type of vessel<br>Class<br>Yard<br>Yard number<br>Year of build  | 25m Workboat Support Vessel<br>MCA Cat 1; 150 miles offshore<br>Havyard, Norway<br>123<br>Delivery May 2017  |
|---------------------------------------|--|--|
| Dimensions:                           | LOA<br>Beam<br>Depth<br>Draft (approx)   | 25 m<br>9.7 m<br>3.5 m<br>2.2 m  |
| Tank Capacities:                      | Fuel<br>Fresh water<br>Transfer pumps<br>Ballast   | 75 m <sup>3</sup> 20 m <sup>3</sup> 32 m <sup>3</sup> /hr 60 m <sup>3</sup>  |
| Performance:                          | Speed<br>Bollard pull  | 12.5 kts (max)<br>15 ton (tbc)   |
| Propulsion System /<br>Aux Equipment: | Main engines Total power Propellers  Bow thruster Generator sets   | 2 x Caterpillar C18 1200 hp Twin screw, fixed pitch 1400 mm props in nozzle with high lift rudders 250 hp 1 x 130 kVA and 1 x 40 kVA   |
| Deck Layout                           | Deck crane mid Deck crane aft Towing winch Anchor handling winch Tugger winch Chain stopper Deck area/dimensions Dry hold Deck cargo Container capacity              | 48 ton/m; max outreach 18.5 m with remote 100 ton/m; max outreach 22 m with remote 20 ton 20 ton (Brake capacity of 40T) 8 ton SWL 50 ton 139 m²; 14.6 m x 9.5 m 40 m³ 115 ton 4 x 20 ft containers with deck fittings |
| Accommodation:                        | 6 persons  3 x 2 berth cabins  Changing/drying area with toilet and laundry facility  Separate galley / mess room / lounge  Extra modular accommodation is available |  |